


N-Channel Enhancement Mode Field Effect Transistor

Product Summary

- V_{DS} 100V
- I_D 65A
- $R_{DS(on)}$ (at $V_{GS}=10V$) <8.6 mohm
- $R_{DS(on)}$ (at $V_{GS}=4.5V$) <11.5 mohm
- 100% EAS Tested
- 100% ∇V_{DS} Tested



General Description

- Low $R_{DS(on)}$ & FOM
- Extremely low switching loss
- Excellent stability and uniformity
- Fast switching and soft recovery
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- Consumer electronic power supply
- Motor control
- Synchronous-rectification
- Isolated DC/DC convertor
- Invertors

Absolute Maximum Ratings ($T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-source Voltage	V_{DS}	100	V
Gate-source Voltage	V_{GS}	± 20	V
Drain Current	I_D	65	A
		41	
Pulsed Drain Current ^A	I_{DM}	260	A
Avalanche energy ^B	EAS	169	mJ
Total Power Dissipation ^C	P_D	96	W
		38.4	
Junction and Storage Temperature Range	T_J, T_{STG}	-55~+150	°C

Thermal resistance

Parameter	Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient ^D	$R_{\theta JA}$	15	20	°C/W
Thermal Resistance Junction-to-Ambient ^D		45	55	
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	1.0	1.3	

Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJD65G10A	F1	YJD65G10A	2500	/	25000	13"Reel



YJD65G10A

■ Electrical Characteristics ($T_j=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	100			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}}=100\text{V}, V_{\text{GS}}=0\text{V}$			1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{\text{GS}}= \pm 20\text{V}, V_{\text{DS}}=0\text{V}$			± 100	nA
Gate Threshold Voltage	$V_{\text{GS(th)}}$	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=250\mu\text{A}$	1.3	1.8	2.5	V
Static Drain-Source On-Resistance	$R_{\text{DS(ON)}}$	$V_{\text{GS}}= 10\text{V}, I_{\text{D}}=20\text{A}$		7.5	8.6	$\text{m}\Omega$
		$V_{\text{GS}}= 4.5\text{V}, I_{\text{D}}=20\text{A}$		9.0	11.5	$\text{m}\Omega$
Diode Forward Voltage	V_{SD}	$I_{\text{S}}=20\text{A}, V_{\text{GS}}=0\text{V}$			1.3	V
Maximum Body-Diode Continuous Current	I_{S}				65	A
Gate resistance	R_{G}	f= 1 MHz, Open drain		0.68		Ω
Dynamic Parameters						
Input Capacitance	C_{iss}	$V_{\text{DS}}=50\text{V}, V_{\text{GS}}=0\text{V}, f=1\text{MHz}$		2270		pF
Output Capacitance	C_{oss}			797		
Reverse Transfer Capacitance	C_{rss}			36		
Switching Parameters						
Total Gate Charge	Q_{g}	$V_{\text{GS}}=10\text{V}, V_{\text{DS}}=50\text{V}, I_{\text{D}}=25\text{A}$		32		nC
Gate-Source Charge	Q_{gs}			11.1		
Gate-Drain Charge	Q_{gd}			4.78		
Reverse Recovery Chrage	Q_{rr}	$I_{\text{F}}=20\text{A}, dI/dt=100\text{A/us}$		64		ns
Reverse Recovery Time	t_{rr}			51.5		
Turn-on Delay Time	$t_{\text{D(on)}}$			9.3		
Turn-on Rise Time	t_{r}	$V_{\text{GS}}=10\text{V}, V_{\text{DD}}=50\text{V}, I_{\text{D}}=25\text{A}$ $R_{\text{GEN}}=2.2\Omega$		34.8		ns
Turn-off Delay Time	$t_{\text{D(off)}}$			24.6		
Turn-off fall Time	t_{f}			71		

- A. Repetitive rating; pulse width limited by max. junction temperature.
- B. $V_{\text{DD}}=50\text{V}$, $R_{\text{G}}=25\Omega$, $L=0.5\text{mH}$, $I_{\text{AS}}=26\text{A}$.
- C. P_{d} is based on max. junction temperature, using junction-case thermal resistance.
- D. The value of $R_{\theta\text{JA}}$ is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The Power dissipation P_{DSM} is based on $R_{\theta\text{JA}} \leq 10\text{s}$ and the maximum allowed junction temperature of 150°C . The value in any given application depends on the user's specific board design.



■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. : On-Resistance vs. Drain Current and Gate Voltage




Figure6. Normalized On-Resistance




Figure7. Drain current




Figure8.Safe Operation Area




Figure9.Normalized Maximum Transient thermal impedance





Figure 10. Power dissipation



■ TO-252-B Package information



SYMBOL	INCHES			Millimeter		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A1	0.000	---	0.008	0.000	---	0.200
A2	0.087	0.091	0.094	2.200	2.300	2.400
A3	0.035	0.039	0.043	0.900	1.000	1.100
b	0.026	0.030	0.034	0.660	0.760	0.860
c	0.018	0.020	0.023	0.460	0.520	0.580
D	0.256	0.260	0.264	6.500	6.600	6.700
D1	0.203	0.209	0.215	5.150	5.300	5.450
D2	0.181	0.189	0.195	4.600	4.800	4.950
E	0.390	0.398	0.406	9.900	10.100	10.300
E1	0.236	0.240	0.244	6.000	6.100	6.200
E2	0.203	0.209	0.215	5.150	5.300	5.450
e	0.090BSC			2.286BSC		
L	0.049	0.059	0.069	1.250	1.500	1.750
L1	0.035	---	0.050	0.900	---	1.270
L2	0.055	---	0.075	1.400	---	1.900
L3	0.240	0.310	0.039	0.600	0.800	1.000
L4	0.114REF			2.900REF		
θ	0°	---	10°	0°	---	10°

NOTE:

- 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
- 2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
- 3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.