


N-Channel Enhancement Mode Field Effect Transistor



PDFN5060-8L

Product Summary

- V_{DS} 40V
- I_D 310A
- $R_{DS(ON)}$ (at $V_{GS}=10V$) $<0.95m\Omega$
- 100% EAS Tested
- 100% ∇V_{DS} Tested

General Description

- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free
- Part no. with suffix "Q" means AEC-Q101 qualified

Applications

- Power switching application
- Uninterruptible power supply
- DC-DC convertor

Absolute Maximum Ratings ($T_A=25^\circ C$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	40	V
Gate-source Voltage		V_{GS}	± 20	V
Drain Current	$T_c=25^\circ C$	I_D	310	A
	$T_c = 100^\circ C$		231	
	$T_A=25^\circ C$		40	
	$T_A = 100^\circ C$		30	
Pulsed Drain Current ^A		I_{DM}	930	A
Avalanche energy ^B		EAS	460	mJ
Total Power Dissipation ^C	$T_c=25^\circ C$	P_D	166	W
	$T_c = 100^\circ C$		83	
	$T_A=25^\circ C$		3	
	$T_A = 100^\circ C$		1.5	
Junction and Storage Temperature Range		T_J, T_{STG}	-55~+175	°C

Thermal resistance

Parameter		Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient ^D	Steady-State	$R_{\theta JA}$	40	50	°C/W
Thermal Resistance Junction-to-Case	Steady-State	$R_{\theta JC}$	-	0.9	

Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJG310G04HJRQ	F1	310G04HJR	5000	10000	100000	13" reel



YJG310G04HJRQ

■ Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	40	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}}=40\text{V}, V_{\text{GS}}=0\text{V}$	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{\text{GS}}= \pm 20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	± 100	nA
Gate Threshold Voltage	$V_{\text{GS(th)}}$	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=250\mu\text{A}$	2.0	2.7	4.0	V
Static Drain-Source On-Resistance	$R_{\text{DS(ON)}}$	$V_{\text{GS}}=10\text{V}, I_{\text{D}}=20\text{A}$		0.78	0.95	$\text{m}\Omega$
Diode Forward Voltage	V_{SD}	$I_{\text{S}}=20\text{A}, V_{\text{GS}}=0\text{V}$		0.76	1.3	V
Gate resistance	R_{G}	f=1MHz		1.6		Ω
Dynamic Parameters						
Input Capacitance	C_{iss}	$V_{\text{DS}}=25\text{V}, V_{\text{GS}}=0\text{V}, f=1\text{MHz}$	-	5800	-	pF
Output Capacitance	C_{oss}		-	2000	-	
Reverse Transfer Capacitance	C_{rss}		-	110	-	
Switching Parameters						
Total Gate Charge	Q_{g}	$V_{\text{GS}}=10\text{V}, V_{\text{DS}}=15\text{V}, I_{\text{D}}=155\text{A}$	-	130	-	nC
Gate-Source Charge	Q_{gs}		-	38	-	
Gate-Drain Charge	Q_{gd}		-	28	-	
Reverse Recovery Charge	Q_{rr}	$I_{\text{F}}=155\text{A}, di/dt=100\text{A/us}$	-	210	-	nC
Reverse Recovery Time	t_{rr}		-	120	-	ns
Turn-on Delay Time	$t_{\text{D(on)}}$	$V_{\text{GS}}=10\text{V}, V_{\text{DD}}=15\text{V}, I_{\text{D}}=155\text{A}$ $R_{\text{GEN}}=3.3\Omega$	-	18	-	ns
Turn-on Rise Time	t_{r}		-	220	-	
Turn-off Delay Time	$t_{\text{D(off)}}$		-	70	-	
Turn-off fall Time	t_{f}		-	23	-	

- A. Repetitive rating; pulse width limited by max. junction temperature.
- B. $T_J=25^\circ\text{C}, V_{\text{DD}}=30\text{V}, V_{\text{G}}=10\text{V}, R_{\text{G}}=25\Omega, L=0.5\text{mH}, I_{\text{AS}}=46.9\text{A}$.
- C. P_d is based on max. junction temperature, using junction-case thermal resistance.
- D. The value of R_{GJA} is measured with the device mounted on 1 in² FR-4 board with 2oz. Copper, in the still air environment with $T_A=25^\circ\text{C}$. The maximum allowed junction temperature of 175°C . The value in any given application depends on the user's specific board design.



■ Typical Electrical and Thermal Characteristics Diagrams




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance Characteristics




Figure 4. Gate Charge




Figure 5. On-Resistance vs Gate to Source Voltage




Figure 6. Normalized On-Resistance




Figure 7. RDS(on) VS Drain Current




Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation




Figure 13. Maximum Transient Thermal Impedance








Figure 14. Safe Operation Area



■ PDFN5060-8L-0.95MM Package information

Top View
正面视图Bottom View
背面视图Side View
侧面视图

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
D	5.15	5.35	5.55
E	5.95	6.05	6.15
A	0.85	0.95	1.05
A1	0.203	BSC	
A2			0.08
D1	4.25	4.35	4.45
E1	3.525	3.625	3.725
D2		5.20	
E2		5.55	
L1	0.45	0.55	0.65
L2	0.68	BSC	
b	0.3	0.4	0.5
e	1.27	BSC	

Suggested Solder Pad Layout
Top View

Note:

1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.10 mm.
3. The pad layout is for reference purposes only.



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.